

## HCAM

### HEVC 4K UHD Camera Transmitter

The HCAM represents the next generation of flexible, portable, HEVC 4K UHD, HDR ready wireless systems from Vislink. With highly flexible and configurable mounting options and video interfaces, the unit can be mounted to broadcast cameras for sporting events, ENG cameras for news and even prosumer cameras for ultimate application flexibility. With user interchangeable RF modules and a range of software options, the HCAM continues the line of innovative, high performance wireless camera systems from Vislink.



### Key Features

- HEVC/4K UHD Very Low Latency Encoder
- HDR Ready
- Interchangeable, futureproof, dual SFP modules supporting Quad 3/6/12G SDI/HDMI/Fiber Optic/SMPTE 2022-6 HD-SDI over IP interfaces
- Integrated Camera Control with FocalPoint Compatibility
- Optional direct-docking V-Lock & Anton Bauer battery plates with integral power feed through
- Compatible with L1750 RF module<sup>1</sup>
- ETSI compliant to proposed EN302-064 V2.1.1 regulations
- Remote control over WiFi via web interface

<sup>1</sup>Requires software change.

### Typical Applications

- Event Coverage
- Newsgathering
- Sports Coverage
- PoV Cameras

### Frequency Band

- 1.300–1.700 GHz\*
- 1.950–2.700 GHz\*
- 3.200–3.900 GHz\*
- 4.400–5.000 GHz
- 6.425–7.125 GHz
- 6.800–7.500 GHz
- 7.200–7.750 GHz

\*pre-distortion correction

### Transmit Power

- Adjustable 10 to 250 mW (or add Barrel Booster option)<sup>1</sup>

### Transmit Antenna

- Omni Directional 3 dBi gain (nom.)

### Frequency Selection

- Up to 16 pre-set channels for tuning

### Modulation

- COFDM DVB-T
- LMS-T

### UHF Receiver

- 410 to 490 MHz frequency range
- FocalPoint camera control compatibility

### Modulation Modes

- QPSK, 16QAM, 64QAM
- FEC:
- 1/2, 2/3, 3/4, 5/6, 7/8, 9/10, 14/15
- Guard interval:
- 1/32, 1/16, 1/8, 1/4

### Data Rate

- DVB-T 4.98 to 31.7 Mbit/s
- LMS-T up to 43 Mbit/s, bandwidth dependent (licensed option)

### Bandwidth

- DVB-T at bandwidths of 6/7/8 MHz
- LMS-T bandwidths of 3/4/5/6/7/8/10/12/14/16/20 or 24 MHz with two carrier density options
- Optional digital pre-distortion for enhanced adjacent channel performance\*

\*frequency permitting

### Video Encoder Profiles

- H.265 HEVC Main, Main 10, Main 4:2:2 10
- H.265 HEVC 8/10 bit to 4K p60
- H.264 AVC Main, High, Baseline up to Level 5.2
- H.264 AVC High 10/4:2:2
- H.264 AVC 4:2:0/4:2:2 8/10 bit to HD p60
- 4K Native and UHD (1 Service)
- HD (Up to 4 Services)<sup>5</sup>
- 1.0–90 Mbps (per channel with maximum combined rate of 90 Mbps)
- SD (Up to 4 Services)
- 4.2.0 Main 0.5–90 Mbps
- 4.2.2 Main 2.0–90 Mbps

### Video Inputs

- 2 SFP+ module slots supporting electrical and optical interfaces carrying:
- 4 x SDI SMPTE-259M
- 4 x HD-SDI SMPTE-292M
- 4 x 3G-SDI SMPTE-424M
- 2 x 6G-SDI SMPTE ST-2081
- 1 x 12G-SDI SMPTE ST-2082

### Video Formats

- 480i@29.97
- 576i@25
- 720p@50/59.94/60
- 1080i@50/59.94/60
- 1080p@23.98/24/25/29.97/30/50/59.94/60
- 2160p@23.98/24/25/29.97/30/50/59.94/60

### Audio Inputs

- Embedded audio over SDI/HD-SDI/3G SDI/6G SDI/12G SDI
- 1x analogue audio stereo pair (Lemo)
- Mic / Line level support with phantom power

### Encoding

- HEVC (H.265)
- AVC (H.264)
- MPEG-2 (H.262)
- AAC
- MPEG-1
- AES / Dolby Passthrough

### Power

- Power supply via Lemo e.g. to connect to D-Tap power source
- Extended operation voltage range 10V to 32.2V
- Optional Anton Bauer and IDX battery plates

### Power Consumption

- Nominally 25W in standard configuration (with L1750-1927)

### ASI

- Input for service multiplexing (Remux)
- Output
- Input and Output on multifunction pins

### PIDS

- PIDs user configurable

### Latency

- 70ms (4K UHD p50)<sup>2</sup>

### Size & Weight

- 165 (L) x 43 (H) x 82 (W) mm<sup>3</sup>
- 600g<sup>4</sup>

### Environmental

- Temperature
- Operating 0°C to 50°C (32°F to 122°F)

### User Interface

- OLED display for enhanced visibility

### Notes

- Some features specified are available via optional licenses.
- Not all encoder interface options are concurrently available.
- We reserve the right to change specifications at any time without prior notice.
- <sup>1</sup>We recommend using the optional D-TAP cable to power the Barrel Booster.
- <sup>2</sup>H.264/MPEG-2 format and latency support timescales TBA.
- <sup>3</sup>Including removable heatsink mounts, excluding RF connectors.
- <sup>4</sup>Including removable heatsink, excluding antennas.
- <sup>5</sup>HD Services 2 to 4 can be enabled via optional licenses.

