

At the heart of the action.

LiveLink Datasheet

LiveLink WMT Bonded **Cellular Transmitter**



Key features

- 1x 12G SDI video input 0
- 4:2:0, 8-bit and 4:2:2 10-bit HEVC 0 encoding
- o HD and 4k UHD p50/p60 resolutions
- 8x 5G bonded cellular modems ο
- Ethernet and Wi-Fi bonding connectivity 0
- Private (Standalone/NPN) 5G Capable ο
- Camera Control 0
- Intercom 0
- Multi-Camera/Transmitter Synchronization 0

Typical applications

- Newsgathering 0
- Live Events 0
- Sports Events 0

The WMT LiveLink is a new generation of bonded cellular encoders that provides class-leading video quality in combination with ultra-reliable, low latency transmission.

With capability for high quality 4:2:2, 10-bit HEVC video encoding up to 4k resolutions, the WMT LiveLink is well-equipped to cover all mobile camera applications from news to critical live events.

The WMT LiveLink's small size makes the device highly transportable and easy to mount to an ENG camera without affecting camera balance and handling or alongside mirrorless camera systems.

With support for up to 8x public cellular connections, in addition to WiFi and public internet, the WMT LiveLink provides market-leading bonding connectivity. Additionally, the WMT LiveLink interfaces seamlessly with Vislink's Private 5G connectivity solution - allowing high data rate connectivity even in heavily populated environments.



LiveLink Datasheet

	LiveLink
RF Transmission	
Transmission System	5G NR, 4G LTE
Frequency Bands	5G NR Sub-6: n1, n2, n3, n5, n7, n8, n12, n20, n25, n28, n38, n40, n41, n48, n66, n71, n77, n78, n79 4G LTE Cat-20: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B18, B19, B20, B21, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B43, B46, B48, B66, B71
Connectivity	
No. of SIM Cards (3G/4G)	8 modems
Wi-Fi	\checkmark
Ethernet Ports	2
Satellite Support	BGAN/Starlink (extra w/sw license)
Video Inputs	
1x 4k, 12G SDI Video Inputs	12G SDI up to 4k p50/60
Video Formats	
HD	480i50
	576i50
	720p@50/59.94/60
	1080i@50/59.94/60
	1080p@23/24/25/29/30/50/59.94/60
4k	UHDp@23/24/25/29/30/50/59.94/60
Audio Inputs	
Embedded Audio	4x Embedded Audio
Video Compression	
HEVC Encoding	4:2:2 Chroma, 10-bit Luma
Encryption	AES-256



Learn more at www.vislink.com

	LiveLink
Error Correction	
i) AARQ (Adaptive Automatic Retransmission Request)	\checkmark
ii) WMT (Wireless Multiplex Technology)	\checkmark
Hosted Management	
LinkMatrix Compatible	\checkmark
Social Media for Cloud Decoding	\checkmark
Accessories	
Dome Antennas	\checkmark
Backpacks	\checkmark
Camera Mount Kits	\checkmark



© Copyright 2023 Vislink Technologies, Inc. All rights reserved. All other products or services referenced herein are identified by the trademarks or service marks of their respective companies or organizations. We reserve the right to change specifications without notice. Where applicable, versions of this device may not have been approved by the Federal Communications Commission (FCC). Where applicable, these versions are not offered for sale or lease until approval of the FCC has been obtained.