

With the **WMT LiveLink**, Vislink leads the next level in bonded cellular live production technology. The LiveLink provides class-leading video quality in combination with ultra-reliable, low latency transmission. With the capability for 4x HD or 1x UHD 4:2:2, 10-bit HEVC HDR video encoding, the WMT LiveLink is well-equipped to cover all mobile camera applications, from multi-camera sports to critical live events.

With its support for return video using a separate SDI output, the WMT LiveLink is a powerful remote production device housed in a cigar box-sized package. The WMT LiveLink's small size makes the device highly transportable and easy to mount to an ENG camera without affecting camera balance and handling or alongside camera systems.

With support for up to 6x public cellular connections, in addition to WiFi and public internet, the WMT LiveLink provides market-leading bonding connectivity. Additionally, the WMT LiveLink interfaces seamlessly with Vislink's Private 5G connectivity solution — allowing high data rate connectivity even in heavily populated environments.

## **Key features**

- 4x 3G or 1x 12G SDI video input
- o 4:2:0, 8-bit and 4:2:2 10-bit HEVC encoding
- Supports 720P50/60, 1080P50/60, 1080i50/60\*,2160P50/60
- 6x 5G bonded cellular modems
- Ethernet and Wi-Fi bonding connectivity
- o Private (Standalone/NPN) 5G Capable
- Camera Control
- o Intercom
- o Multi-Camera/Transmitter Synchronization
- o SDI output for video return

\*H.265 only

## **Typical applications**

- Newsgathering
- o Live Events
- Sporting Events
- o Remote Production



	LiveLink
RF Transmission	
Transmission System	5G NR, 4G LTE
Frequency Bands	5G NR  Sub-6: n1, n2, n3, n5, n7, n8, n12, n20, n25, n28, n38, n40, n41, n48, n66, n71, n77, n78, n79  4G LTE  Cat-20: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B18, B19, B20, B21, B25, B26, B28, B29,  B30, B32, B34, B38, B39, B40, B41, B42, B43, B46, B48, B66, B71
Connectivity	
No. of SIM Cards (3G/4G)	6 modems
Wi-Fi	
Ethernet Ports	2
Satellite Support	BGAN/Starlink (extra w/sw license)
Video Inputs	
4x 3G or 1x 12G SDI video input	12G SDI up to 4K UHD p50/60
Video Formats	
HD	720P @50/59.94/60
	1080i @50/59.94/60
	1080P @23/24/25/29/30/50/59.94/60
4K	UHDP @23/24/25/29/30/50/59.94/60
Audio Inputs	
Embedded Audio	4x Embedded Audio
Video Compression	
HEVC Encoding	4:2:2 Chroma, 10-bit Luma
Encryption	AES-256



## **LiveLink Datasheet**

	LiveLink
Error Correction	
i) AARQ (Adaptive Automatic Retransmission Request)	
ii) WMT (Wireless Multiplex Technology)	
Hosted Management	
LinkMatrix Compatible	
Social Media for Cloud Decoding	
Accessories	
Dome Antennas	
Backpacks	
Camera Mount Kits	

