

**TRANSMITTER**

# INCAM-GV 5G

Grass Valley HEVC 4K UHD 5G  
Wireless Camera Transmitter



The Vislink INCAM GV 5G is a fully integrated HEVC 4K UHD, HDR-ready wireless video transmitter and receiver, designed for use with Grass Valley's LDX 100 Series live production cameras. The INCAM GV 5G leverages the capabilities of private 5G cells in studios and stadiums, as well as public sliced 5G networks. It complements the latest design enhancements incorporated into the Grass Valley LDX 100 Series cameras for heightened usability and ergonomic operation.

The INCAM GV 5G delivers broadcast-quality encoding at multiple resolutions including 4K UHD, 1080p, 1080i and 720p. It facilitates the bonding of multiple IP connections in real time, enabling a blend of cabled and wireless applications at various venues. This enables seamless transition between wired and wireless operations during live broadcasts, enhancing reliability with hot failover capabilities.

Broadcast organizations can leverage the INCAM GV 5G's HEVC video coding technology to transmit high-quality images efficiently, even over minimal 5G bandwidth or constrained IP connections like Starlink and traditional wired networks.

With support for dual 5G cellular connections, in addition to WiFi and wired internet options, the INCAM GV 5G provides market-leading bonding connectivity and enables roaming between public and private 5G networks.

## Key Features

---

HEVC/4K UHD Very Low Latency Encoder

---

HDR Ready

---

10-bit 4:2:2

---

FocalPoint compatible internal IP-based  
Camera Control

---

Remote control over Wi-Fi via web  
interface

---

2 × 5G modems supporting Private 5G

---

Data bonding supporting transparent IP  
connection

---

Return vision

---

Intercom functionality

---

Data channels for third-party devices  
including DMX lighting systems or robotic  
head controls to facilitating remote  
production setups

---

## Typical Applications

---

Event Coverage

---

Newsgathering

---

Sports Coverage

---

Studio Cameras

# INCAM-GV 5G Datasheet



Technical Specifications	
RF Output	
Modulation	ISDB-T, LMS-T, DVB-T, DVB-T2*
RF Frequency Output	Wideband 1.95-3GHz / 3.0-4.0GHz/ 4.0-5.0GHz/ 5.0-6.0GHz/ 6.0-7.5GHz*
RF Output Power	50 or 100 mW
Video Inputs	
1x HD/4K internal video connection	yes
Video Formats	
1x HD	480i50; 576i50; 720p@50/59.94/60; 1080i@50/59.94/60; 1080p@23/24/25/29/30/50/59.94/60
1x 4K	UHDp@23/24/25/29/30/50/59.94/60
Audio Inputs	
Embedded Audio	4x Embedded Audio
Video Compression	
HEVC Encoding	4:2:2 Chroma, 10-bit Luma
Audio Compression	
AAC and MPEG1 L2	yes
Remote Control	
WiFi remote control	Web browser
UHF Telemetry	Remote control commands
Telemetry	
UHF Input	410 to 490 MHz FSK over FM modulation
Camera Power and Control	
FocalPoint Control	Internal IP-based Camera Control
Power	
DC Power	Internally powered by the camera, controlled by camera on-off switch
Physical Connectors	
RF Out	SMA
UHF	N-connector

\* *Licensable*

E: [sales@vislink.com](mailto:sales@vislink.com) T: +1 908 852 3700 / + 44 1442 431300 [www.vislink.com](http://www.vislink.com)

© Copyright 2024 Vislink LLC and Vislink Poway LLC are Vislink Technologies, Inc. companies. All rights reserved. All other products or services referenced herein are identified by the trademarks or service marks of their respective companies or organizations. We reserve the right to change specifications without notice. Where applicable, versions of this device may not have been approved by the Federal Communications Commission (FCC). Where applicable, these versions are not offered for sale or lease until approval of the FCC has been obtained.